OD)

FEB- 1952 51-4AA

5X1 5X1 STATE ARMY	Weight 580 Diameter 1,m	uirements: 2 sepower. Com acement is 26 mm. 415 (?) kgs. (?)	is 660 horsep	ower.	າ ກ່ວນກ at 80	meters
5X1	Carburetor Requested for maximum hore cylinder displant Stroke 1,m Weight 580 Diameter 1,m	uirements: 2 sepower. Com acement is 26 mm. 415 (?) kgs. (?)	25 grams per l pression ratio ,821 (?).	ower.	າ ກ່ວນກ at 80	meters
	Carburetor Requested of maximum hor cylinder displements of the stroke length of the stroke l	uirements: 2 sepower. Com acement is 26 mm. 415 (?) kgs. 388 (?)	25 grams per l pression ratio ,821 (?).	ower.	າ ກ່ວນກ at 80	meters
	Carburetor Req of maximum hor cylinder displ Bore 154 Stroke 1,m Weight 580	uirements: 2 sepower. Com acement is 26 mm. 415 (?) kgs.	25 grams per l pression ratio ,821 (?).	ower.	າ ກ່ວນກ at 80	meters
	Carburetor Req of maximum hor cylinder displ Bore 154 Stroke 1,m Weight 580	uirements: 2 sepower. Com acement is 26 mm. 415 (?) kgs.	is 660 horsep	ower.	າ ກ່ວນກ at 80	meters
	Carburetor Req of maximum hor cylinder displ	uirements: 2 sepower. Com acement is 26 mm. 415 (?)	is 660 horsep	ower.	າ ກ່ວນກ at 80	meters
	Carburetor Required of maximum hor cylinder displ	uirements: 2 sepower. Com	is 660 horsep	ower.	າ ກ່ວນກ at 80	meters
	Carburetor Req	uirements: 2	is 660 horsep	ower.	າ ກ່ວນກ at 80	meters
	altitude the n	ne, engine peri naximum power	is 660 horsep	ower.	າ ກ່ວນກ at 80	meters
	merers arrith	ie, engine perf	orms at 840 h is 660 horsep	ower.	. At 4,800	meters
	merers arrith	ie, engine perf	orms at 840 h is 660 horsep	ower.	. At 4,800	meters
	merers arrith	ie, engine perf	orms at 840 h is 660 horsep	ower.	. At 4,800	meters
	merers arrith	ie, engine perf	orms at 840 h	ower.	. At 4,800	meters
5X1	merers arrith	ie, engine perf	orms at 840 h is 660 horsep	ower.	. At 4,800	meters
5X1	merers arrith	ie, engine perf	orms at 840 h	or achower.	. At 4,800	meters
			epower. In c	limb or i	n combat, at	3 (00
	1				7	
5X1						
~ •	The specifications are	s of this engi Listed below:	ne			
X1 2.	turn right with re		-			
	Sovremtractor pro- air cooled injects	or motor with	9 cvlinders i	type KLM n line,2	10. This is The propell	ers
X1 ,	Souromtreetor	disagn on silve				<i>-</i>
OHIBITED BY I	AW. THE REPRODUCTION OF THIS FO	RM IS PROHIBITED.			·	HAIN!
THE UNITED S D 794, OF THE	STATES, WITHIN THE MEANING OF TITLE E U.S. CODE, AS AMENDED. ITS TRAN CONTENTS TO OR RECEIPT BY AN UNAUT	18, SECTIONS 793	THIS IS	UNEVALU	ATED INFORM	IATION
IIS DOCUMENT (ONTAINS INFORMATION AFFECTING THE	NATIONAL DEFENSE				
CQUIRED		NOT_C	CIRCULATE	25X1	SUPPLEMENT REPORT NO.	
LACE		NOT C			-	·
ATE OF NFO.	20/(1				NO. OF ENCLS	
000001	Sovrom Produced K	IM IO Alrerai		in s.	NO. OF PAGES	2
UBJECT		TIM TO 11	-		DATE DISTR.	31 October 19
OUNTRY	Discourant in					
					CD NO.	
		INFUKM	ATION RE	PORT	REPORT	25X1
					25X1	05)/4
	CLASSIFICATION (SECRET,			25.74	

4	ú	SECRET				
		- 2 -				
	3.	The gear case is in two parts and is in light metal; the other parts are in light casting. Pistons and cylinder heads are in light metal. Bolts are protected by aluminum covering.	•			
25X	1	Comment. There has been no previous information on an aircraft type KLM 10.				

25X1

Comment. Attention is drawn to the unlikelihood of an in-line engine having nine cylinders. It would also appear strange that an engine of this power should be in-line air-cooled.

Approved For Release 2004/07/08 : CIA-RDP82-00457R014700070001-5

25X1

25X1